



Printing date 22.03.2013 Revision: 22.03.2013

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: MINERALNI ZARIBAN OMET
- · Article number: MLZ ver. 7
- · Relevant identified uses of the substance or mixture and uses advised against

Decorative plaster for outer walls MINERALNI ZARIBAN OMET, MLZ ver. 7; Edelputz; MINERAL TROWELLED RENDER

· Product category

Products MINERALNI GLAJEN OMETI / MINERAL TROWELLED RENDERS 2.0 and 2.5 are thin layered noble plasters manufactured on the basis of cement, lime and polymeric binders combination with characteristic evenly grained surface and are intended for decorative protection of inner wall surfaces, as well as the facade surfaces on buildings with height up to two storeys, which have suitably wide projecting roofs and are relatively well protected against rainfall.

· Application of the substance / the preparation

Products MINERALNI ZARIBAN OMET plasters are distinguished by high values of vapour permeability, grasp ability, relatively good resistance to the effects of smoke gases and UV rays, and may be installed as final plasters in the contact facade thermal-insulation systems on the mineral wool.

Use of mineral plasters provides long-term resistance of surfaces against contaminations with wall algae and mould; therefore addition of biocidal substances prior to installation is not required.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

JUB d.o.o.

Dol pri Ljubljani 28

1262 DOL PRI LJUBLJANI

SLOVENIA

T: + 386 1 5884 183

F: + 386 1 5884 250

E: info@jub.si

· Further information obtainable from:

Product safety department:

 $TRC\ JUB\ d.o.o.$

Branko Petrovic, MSc

T: +386 1 5884 185

F: +386 1 5884 227

E: branko.petrovic@trc-jub.si

· Emergency telephone number:

During normal opening times (8 - 16h CET) Group JUB: +386 1 5884 185

United Kindom: NPIS 0870 600 6266

2 Hazards identification

· Classification of the substance or mixture

The product is classified as a dangerous irritative mixture and harmful for the environment in accordance with the regulation on classification of chemicals (rules on classification and particularly EU Directives 1967/548/EC and 1999/45/EC, obliged to the Regulation CLP 2008/1272/EC), due to the defined content of cement, lime and algaecide.

· Classification according to Regulation (EC) No 1272/2008



Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi;

Xi; Irritant

R37/38-41: Irritating to respiratory system and skin. Risk of serious damage to eyes.

×

Xi; Sensitising

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

· Hazard-determining components of labelling:

Cement, portland, chemicals calcium dihydroxide terbutryn

· Risk phrases:

37/38 Irritating to respiratory system and skin.

- 41 Risk of serious damage to eyes.
- 43 May cause sensitisation by skin contact.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

- 2 Keep out of the reach of children.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37/39 Wear suitable gloves and eye/face protection.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

GE

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

The product is a chemical mixture of mineral binders, polymeric emulsion and inorganic fillers. Major components of mineral plasters: cement, hydrated lime, polymeric binder, quartz and calcite fillers, cellulose thickener.

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 65997-15-1	Cement, portland, chemicals	15.0-25.0%
EINECS: 266-043-4	Xi R37/38-41;	
	Eye Dam. 1, H318; 🗘 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 1305-62-0	calcium dihydroxide	4.0-8.0%
EINECS: 215-137-3	X Xi R38-41	
	🥎 Eye Dam. 1, H318; 아 Skin Irrit. 2, H315	
CAS: 886-50-0	terbutryn	< 0.1%
EINECS: 212-950-5	¥ N R50/53	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 💠 Acute Tox. 4, H302	

· Additional information:

The product is is water borne alkyd impregnation of wood containing with biocidal substances for wood preservation against molds, wood rot and insects.

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: CO2, sand, extinguishing powder. Do not use water.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Pick up mechanically.
- · Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

· Further information about storage conditions:

Store under lock and key and with access restricted to technical experts or their assistants only.

- · Storage class: Storage class: 12 Incombustible solid products
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

1305-62-0 calcium dihydroxide

WEL Long-term value: 5 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	rties
Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Powder
Colour:	Different according to colouring
Odour:	Odourless
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not applicable.
Density at 20 °C:	$1.4 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %
VOC (EC)	0.00 %
	The content of VOC: not defined (the product is not subjected Directive 2004/42/ES).
Solids content:	100.0 %

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

oral. $> 5000 \, mg/kg \, (Rat)$

dermal. > 5000 mg/kg(Rat)

inhal. > 5000 mg/kg (Rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

The mineral plaster should not be disposed with household waste, poured into water, sewage or on the floor. Hardened deposits should be treated as construction waste.

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 6				
· European	European waste catalogue			
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances			
	other construction and demolition wastes (including mixed wastes) containing dangerous			
	substances			
15 01 01	paper and cardboard packaging			

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number	The product MINERALNI ZARIBAN OMET is not a substanc or mixture classified in accordance with the provisions of ADI as dangerous for transport.
· ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· UN ''Model Regulation'':	-

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture Following regulation was considered in the preparation of document:

Legislation on the occupational health and safety, the chemical legislation and regulations on biocidal products, regulations on classification, packaging and labeling of chemical and biocidal products and requirements on safety data sheets for chemicals and biocidal products composition, as well as regulations on the management of packaging and packaging waste and waste.

In accordance with the current regulation the product is classified as a dangerous irritative mixture. The product is dangerous for the environment due to algaecide.

General safety measures should be considered when working or handling with the product.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

(Contd. on page 8)

Printing date 22.03.2013 Revision: 22.03.2013

Trade name: MINERALNI ZARIBAN OMET

(Contd. of page 7)

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing MSDS: Product safety department

· Contact:

Branko Petrovic, MSc.

T: + 386 1 5884 185

E: branko.petrovic@trc-jub.si

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB